Amhaze Stadium



FEATURES

- Professional water-based haze machine.
- 30-sec heat up time nearly eliminates wait time for operation.
- · Adjustable vent louver for directional haze flow.
- Tour-ready with a rugged road case and M12 threaded rigging insert.
- Achieve continuous variable haze output and blower speed, adjusted via DMX or manual knobs.

SPECIFICATIONS

DYNAMIC EFFECTS

Output: 14,000 cfm

· Low Fluid Shutdown: No

CONSTRUCTION/PHYSICAL

Dimensions:

20.60 in (523.42 mm) x 10.80 in (274.9 mm) x 15.97 (405.7 mm)

Weight: 38.4 lb (17.4 kg)

Exterior Color: Black

Tank Capacity: 1.3 gal (4.92l)

Fluid Consumption: 22 ml/min

CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

· Control Protocol: DMX

DMX Channels: 2

Modes/Personalities: 1 personality

· On-Board Control: Yes

ELECTRICAL

Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz

Power and Current: 1,230 W, 10.25 A @ 120 V, 60 Hz

Power and Current: 2,430 W, 10.56 A @ 230 V, 50 Hz

· Heat-up Time: 30 sec

CERTIFICATIONS/QUALIFICATIONS

• CE

IP Rating: IP20, dry location

WHAT'S INCLUDED

Amhaze Stadium

Seetronic Powerkon IP65 power cord

OPTIONAL ACCESSORIES

Clamps

Neutrik® powerCON® cables

DMX Cables

REQUIRED ACCESSORIES

Compatible Mounting Options: M12 Bolt/Clamp

