

# The Light Source

## Uni-Bolt for Strut Channels



The Uni-Bolt fastens fixtures or pipes to strut channel. Insert the Uni-Bolt into the strut channel, rotate 90 degrees and spin the 2" diameter knurled disk to lock into the channel. Also available for 1 5/8" x 13/16" strut channel.

The UB2B works with Uni-Strut product series: P1000, P1100, P2000, P3000, P5000, and P5500

The UB2B2 works with Uni-strut product series: P3300, P4000, and P4100

**Minimum Size** 1 5/8" x 1 5/8" Strut Channel

**Working Load Limit** 250 lbs.

**Hardware** 1/2-13 TPI x 1" Hex Head Cap Screw Grade 5 Zinc Plated.

**Weight** 0.35 lbs.

**Case Quantities** each

**Order Codes**

**UB2B** Uni-Bolt for Strut Channels, Black

**UB2B-M10** Uni-Bolt for Strut Channels with M10 Threads, Black

**UB2W** Uni-Bolt for Strut Channels, White Powder Coat

**UB2B2** Low Profile Uni-Bolt for Strut Channels 1 5/8" x 13/16", Black

**UB2W2** Low Profile Uni-Bolt for Strut Channels 1 5/8" x 13/16", White Powder Coat