



GENERAL INFORMATION

A portable USB to two five-pin XLR interface, Gadget II connects via USB to any computer without a network infrastructure. When used with PC- or Mac-based ETCnomad® controllers, Gadget II outputs levels via DMX and initiates bidirectional communication using RDM. The device can also be used with UpdaterAtor or Net3 Concert software to interact with RDM enabled fixtures or to update ETC devices.

APPLICATIONS

- Houses of worship
- High schools
- Community theaters
- Academic theaters
- Touring
- Tech table
- System integration
- Ideal for venues and applications where single DMX is portable.

FEATURES

- Two DMX/RDM connection using 5-pin female XLR
- Distributes DMX and RDM
- USB connectivity
- USB activity indicators
- Compatible with Net3 Concert software
- Compatible with ETCnomad software
- Compatible with UpdaterAtor software

ORDERING INFORMATION

Gadget

MODEL	DESCRIPTION
GADGET	Two Port USB to DMX/RDM Interface

SPECIFICATIONS

FUNCTIONAL

- Supports RDM (ANSI E1.20)
- USITT DMX512 and ANSI E1.11 DMX512-A compliant

MECHANICAL

- Finished in fine-textured, powder-coat paint with matching overlay
- Two integrated 5-pin XLR DMX output port
- Type B USB female connection
- Activity LED

ENVIRONMENTAL

- Ambient operating temperature: 0° to 40°C (32° to 104°F)
- Operating humidity: 0% - 95% non-condensing

ELECTRICAL

- 5V USB power required
- RoHS Compliant (lead-free)
- CE marked

PHYSICAL

Gadget II Dimensions

MODEL	HEIGHT		WIDTH		DEPTH	
	inches	mm	inches	mm	inches	mm
Gadget	1.75	44	4.20	107	3.25	83

Gadget II Weights

MODEL	WEIGHT		SHIPPING WEIGHT	
	lbs	kgs	lbs	kgs
Gadget	0.50	0.22	0.75	0.34

* Weight without hanging hardware

GADGET II

