



# MicroCom 900XR Product Specifications

BeltPack Models: PMC-900XR, PMC-900XR-AN

## Overview

Rugged and durable, the MicroCom 900XR provides full-duplex, hands-free communication to crews and teams for critical workplace communication. In addition to 10 full-duplex users and two separate talk channels, the 900XR provides unlimited listeners and unlimited shared talk users, all without the need for a basestation. High-quality audio, excellent range, and ease of use make the 900XR a perfect solution for crews to stay connected, be productive, and focus on job safety.

## 900XR BeltPack Key Features

- Robust Two-Channel (A or B) System
- Simple to Operate
- Up to 10 Full-Duplex Users
- Pack-to-Pack Communication
- Unlimited Shared Users
- Unlimited Listen-Only Users
- 900MHz Frequency Band
- Encrypted FHSS Technology
- Ultra Compact, Small, and Lightweight
- Rugged, IP67-Rated BeltPack
- Long, 12-Hour Battery Life
- Field-Replaceable Battery
- Available Drop-In Charger
- Multiple Headset and Earset Options

## What's in the Box?

- BeltPack
- Li-Ion Battery (BT-01)
- USB Charging Cable
- BeltPack Antenna (Attach to beltack prior to operation.)
- Quick Start Guide
- Product Registration Card

## Optional Accessories

- PAC-USB5-CHG: MicroCom 5-Port USB Charger
- PAC-MCXR-5CASE: IP67-rated MicroCom Hard Carry Case
- PAC-MC-SFTCASE: MicroCom Soft Travel Case
- PBT-XRC-55: MicroCom XR 5+5 Drop-In BeltPack and Battery Charger
- Selection of compatible headsets (see 900XR Manual for more details)

Specification*	900XR	900XR-AN**
Radio Frequency Type	902–928 MHz	915–928 MHz
Radio Interface	GFSK with FHSS	
Voice Codec	16 bit / 8 kHz	
Maximum Effective Isotropically Radiated Power (EIRP)	400 mW	
Rx Sensitivity	-95 dBm	
Frequency Channels	52	
Channel Spacing	0.5 MHz	
Number of Intercom Channels	2	
Maximum Full-Duplex Users	10	
Number of Shared Users	Unlimited	
Number of Listen Only Users	Unlimited	
Antenna	Detachable 1 dBi Helical Antenna	
Battery Type	Rechargeable 3.7 V; 2,000 mA Li-ion field-replaceable battery	
Battery Life	Approx. 12 hours	
Battery Charging Time	3.5 hours (USB cable) 6.5 hours (Drop-In charger)	
Charge Type	USB Micro; 5 V; 1–2 A	
Dimension (with Belt Clip)	4.83 in. (H) × 2.64 in. (W) × 1.22 in. (D) [122.7 mm (H) × 67 mm (W) × 31 mm (D)]	
Weight	6.35 oz. (180 g)	
Display	OLED	

Pliant Technologies, LLC  
205 Technology Parkway  
Auburn, Alabama 36830 USA  
www.plianttechnologies.com  
Phone +1.334.321.1160  
Fax +1.334.321.1162

\* Notice about Product Specifications: While Pliant makes every effort to maintain the accuracy of the information contained in this document, this information is subject to change without notice. Please check our website for the latest system specifications and certifications. Performance specifications included in this document are design-centered specifications and are included for customer guidance and to facilitate system installation. Actual operating performance may vary. Manufacturer reserves the right to change specifications to reflect latest changes in technology and improvements at any time without notice.

\*\*PMC-900XR-AN is approved for use in Australia and New Zealand and operates within the 915–928 MHz frequency range.

Copyright ©2020 Pliant Technologies, LLC. All rights reserved. Pliant®, MicroCom®, and the Pliant "P" are trademarks of Pliant Technologies, LLC. All other trademarks are property of their respective owners.

MC900XR\_DATASHEET\_11.11.2020



MicroCom 900XR  
BeltPack

**MICROCOM™**  
900XR