



**SUPERSATURATED**

MSDS No.:5965 - 6003

MSDS Preparation Date: April 1, 2012

Page 1 of 15

**MATERIAL SAFETY DATA SHEET**

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

**Product Name** : **SUPERSATURATED**  
 Supersaturated Red (No. 5965)  
 Supersaturated Green Shoe Blue (No.5968)  
 Supersaturated Ultra Blue (No.5969)  
 Supersaturated Chrome Green (No.5971)  
 Supersaturated Emerald Green (No.5972)  
 Supersaturated Phthalo Green (No.5973)  
 Supersaturated Imperial Green (No. 5974)  
 Supersaturated Magenta (No.5975)  
 Supersaturated Brilliant Red (No. 5976)  
 Supersaturated Spectrum Red (No.5977)  
 Supersaturated Purple (No.5979)  
 Supersaturated Iron Red (No.5980)  
 Supersaturated Chrome Yellow (No.5981)  
 Supersaturated Yellow Ochre (No.5982)  
 Supersaturated Raw Sienna (No.5983)  
 Supersaturated Orange (No.5984)  
 Supersaturated Burnt Umber (No.5985)  
 Supersaturated Raw Umber (No.5986)  
 Supersaturated Burnt Sienna (No.5987)  
 Supersaturated Lemon Yellow (No.5988)  
 Supersaturated Prussian Blue (No.5990)  
 Supersaturated Navy Blue (No.5991)  
 Supersaturated Paynes Gray (No. 5992)  
 Supersaturated Leather (No.5993)  
 Supersaturated Grass Green (No.5994)  
 Supersaturated Cerulean Blue (No.5996)  
 Supersaturated Hunter Green (No.5997)  
 Supersaturated Van Dyke Brown (No.5998)  
 Supersaturated Base - Neutral (No.6001)  
 Supersaturated Base - White (No. 6002)  
 Supersaturated Base - Velour Black (No.6003)

**Product Use** : Paint

**Chemical Family** : Mixture.

**Supplier's name and address:**

**Rosco Laboratories Inc.**

52 Harbor View Avenue  
 Stamford, CT, United States  
 06902

**24 Hr. Emergency Tel #** : (800) 424-9300

**HMIS Rating** : \*- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: \* 1

Flammability: 1

Reactivity: 0

**WHMIS Classes:**



TOXIC



**SUPERSATURATED**

MSDS No.:5965 - 6003

MSDS Preparation Date: April 1, 2012

Page 2 of 15

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

| <u>Ingredients</u>  | <u>CAS #</u> | <u>% (weight)</u> | <u>ACGIH TLV</u>                                 |             | <u>OSHA PEL</u>                                |             |
|---|--------------|-------------------|--|-------------|--|-------------|
|   |              |                   | <u>TWA</u>                                       | <u>STEL</u> | <u>PEL</u>                                     | <u>STEL</u> |
| <b>Supersaturated - Brilliant Red</b><br>Silica, crystalline quartz, respirable dust  | 14808-60-7   | 3.00 - 7.00       | 0.025 mg/m <sup>3</sup><br>(respirable fraction) | N/Av        | (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> | N/Av        |
| <b>Supersaturated - Paynes Gray</b><br>Iron oxide red   | 1309-37-1    | 0.00 - 0.00       | 5 mg/m <sup>3</sup><br>(respirable fraction)     | N/Av        | 10 mg/m <sup>3</sup>                           | N/Av        |
| <b>Supersaturated - Paynes Gray</b><br><b>Supersaturated - Imperial Green</b><br>Carbon black   | 1333-86-4    | 0.10 - 1.00       | 20 ppm   | N/Av        | 50 ppm (240 mg/m <sup>3</sup> )<br>(skin)      | N/Av        |
| <b>Supersaturated Base - Velour Black</b><br>Silica, crystalline-cristobalite   | 14464-46-1   | 3.00 - 7.00       | 0.025 mg/m <sup>3</sup>                          | N/Av        | N/Av   | N/Av        |
| <b>Supersaturated Burnt Umber</b><br>Manganese dioxide  | 1313-13-9    | 1.00 - 5.00       | N/Av   | N/Av        | N/Av   | N/Av        |
| <b>Supersaturated Chrome Green</b><br>Chrome oxide  | 1308-38-9    | 15.00 - 40.00     | N/Av   | N/Av        | N/Av   | N/Av        |
| <b>Supersaturated Chrome Yellow</b><br>Silica, crystalline-cristobalite   | 14464-46-1   | 1.00 - 5.00       | 0.025 mg/m <sup>3</sup>                          | N/Av        | N/Av   | N/Av        |
| Glycol ether  | 111-46-6     | 0.50 - 1.50       | N/Av   | N/Av        | N/Av   | N/Av        |
| <b>Supersaturated Green Shoe Blue, Supersaturated Emerald Green, Supersaturated Navy Blue, Supersaturated Grass Green</b><br>Propylene glycol | 57-55-6      | 1.00 - 5.00       | N/Av   | N/Av        | N/Av   | N/Av        |
| <b>Supersaturated Hunter Green</b><br>Silica, crystalline-cristobalite  | 14464-46-1   | 5.00 - 10.00      | 0.025 mg/m <sup>3</sup>                          | N/Av        | N/Av   | N/Av        |
| <b>Supersaturated Lemon Yellow, Supersaturated Van Dyke Brown, Supersaturated Base - Neutral</b><br>Silica, crystalline-quartz                | 14808-60-7   | 0.10 - 1.00       | 0.025 mg/m <sup>3</sup>                          | N/Av        | (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> | N/Av        |
| <b>Supersaturated Phthalo Green</b><br>1-Propanol, 2-amino-2-methyl-  | 124-68-5     | 0.50 - 1.50       |  |             |  |             |
| <b>Supersaturated White</b><br>No hazardous ingredients   | N/Av         | 0.00 - 0.00       | N/Av   | N/Av        | N/Av   | N/Av        |



SUPERSATURATED

MSDS No.:5965 - 6003

MSDS Preparation Date: April 1, 2012

Page 3 of 15

### SECTION 3 - HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Liquid. Multiple colors. Irritating to eyes, respiratory system and skin. Harmful if inhaled or swallowed Contains material which can cause cancer.

#### \*\*\*POTENTIAL HEALTH EFFECTS\*\*\*

**Target organs** : None reported by the manufacturer.  
**Routes of exposure** : *Inhalation*: YES *Skin Absorption*: YES *Skin & Eyes*:YES *Ingestion*: YES

#### Potential acute health effects :

*Eyes*: Causes eye irritation. May cause conjunctivitis, irritation, and inflammation of mucous membranes. May cause burning sensation, redness and tearing (watering). Possible severe irritation.

*Skin*: Irritating to skin. Possible irritation, defatting or dermatitis (rash). Components of the product may be absorbed into the body through the skin. May cause central nervous system depression.

*Inhalation*: Can cause irritation of the respiratory tract. Prolonged exposure to vapors may be harmful to health. If higher concentrations are inhaled, additional symptoms may include coughing, shortness of breath, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May cause mucous membrane irritation. Other adverse effects: Asphyxia. Severe lung irritation or lung damage, loss of appetite. Sanding and grinding dusts may be harmful if inhaled. Contains particles which may cause lung damage if inhaled in large quantities.

*Ingestion*: Lung aspiration hazard. This product may be aspirated (inhaled) into the lungs during ingestion. May cause lung inflammation. May cause mucous membrane irritation. Ingestion may cause symptoms similar to inhalation. May cause gastrointestinal irritation. Gastrointestinal irritation may include abdominal pain, nausea, diarrhea and vomiting. Other adverse effects: intoxication.

#### Potential chronic health effects

: Prolonged skin contact may defat the skin and produce dermatitis. May cause allergic skin reaction. Harmful by skin absorption. May cause central nervous system depression. Prolonged inhalation of vapors may cause lung damage, including chronic bronchitis. Contains crystalline silica; prolonged exposure by inhalation of particles can cause serious lung damage, including silicosis.

#### Medical conditions aggravated by overexposure

: None expected, when used as intended.

#### Additional health hazards

: Exposure to respirable silica is not possible under normal conditions of use. Crystalline Silica has been classified as a carcinogen in dry powder form only.

#### Potential environmental effects

: None reported by the manufacturer.

### SECTION 4 - FIRST AID MEASURES

**Inhalation** : If breathed in, move person into fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.

**Skin contact** : Flush with plenty of water. Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, seek prompt medical attention.

**Eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, seek prompt medical attention.

**Ingestion** : Call a physician or Poison Control Centre immediately. Do NOT induce vomiting. Guard against aspiration into lungs by having the individual turn on their left side.

**Notes For Physician** : Treat symptomatically.

### SECTION 5 - FIRE FIGHTING MEASURES

#### Fire hazards/conditions of flammability

: Not flammable under normal conditions of handling. This product will not burn, due to its water content.

#### Flammability classification (OSHA 29 CFR 1910.1200)

: OSHA Combustible Liquid IIIB.

#### Flash point

: Not applicable.



**SUPERSATURATED**

MSDS No.:5965 - 6003

MSDS Preparation Date: April 1, 2012

Page 4 of 15

**Flash point Method** : Not applicable. **Auto-ignition temperature** : Not available.  
**Lower flammable limit (% by vol.)** : Not applicable. **Upper flammable limit (% by vol.)** : Not applicable.

**Suitable extinguishing media** : Dry chemical, foam, carbon dioxide and water fog.

**Explosion data: Sensitivity to mechanical impact / static discharge** : Not expected to be sensitive to mechanical impact or static discharge.

**Special fire-fighting procedures/equipment** : Firefighters should wear an approved full-face, self-contained breathing apparatus (SCBA) and impervious clothing. Water may be ineffective on fire, but may be helpful in cooling unburned containers. Do not use a solid water stream as it may scatter and spread fire. If water is used, fog nozzles are preferable.

**Hazardous combustion products** : Oxides of carbon, nitrogen, and sulphur. Oxygen. Acrid fumes, toxic gases.

**Oxidizing properties** : None known.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Avoid breathing vapors. Wear resistant clothing and boots.

**Environmental precautions** : Prevent product from entering drains, sewers, waterways and soil.

**Spill response/cleanup** : Eliminate all ignition sources if safe to do so. Ventilate area of release. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).

**Containment** : Should not be released into the environment. Recover free liquid or cover with inert absorbent material and place into appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

**Safe Handling procedures** : Use with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Wash hands thoroughly after using this product, and before eating, drinking or smoking. Avoid breathing of dust created by cutting, sanding, or grinding. Sanding and grinding dusts may be harmful if inhaled. Do not re-use empty containers. Do not puncture container. Keep in properly labeled containers. Wear suitable protective equipment. Do not ingest.

**Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Do not freeze. Keep container tightly closed when not in use. Store in upright position only. Keep out of the reach of children. Empty product containers may contain hazardous product residue.

**Incompatible materials** : Oxidizing agents. Acids and bases. Aluminum. Ammonium salts. Other: magnesium, chlorinated rubber.

**Special packaging materials** : Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

**SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**Ventilation and engineering measures** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof equipment. Discharge exhaust only in area away from ignition sources.

**Respiratory protection** : Use NIOSH/MSHA approved full-face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

**Skin protection** : Wear impervious gloves, such as neoprene or nitrile rubber.

**Eye / face protection** : Safety glasses with side-shields or chemical splash goggles.



**SUPERSATURATED**

MSDS No.:5965 - 6003

MSDS Preparation Date: April 1, 2012

Page 5 of 15

**Other protective equipment**

: Emergency showers and eyewash facilities should be nearby. Depending on conditions of use, safety shoes and additional protective clothing may also be necessary.

**General hygiene considerations**

: Wash hands thoroughly after using this product, and before eating, drinking or smoking. Wash hands before breaks and at the end of workday.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

|   |   |   |  |
|---|---|---|--|
| <b>Physical state</b>                                   | : Liquid.   | <b>Appearance</b>                             | : Liquid in multiple colors.   |
| <b>Odor</b>   | : Not available.  | <b>Odor threshold</b>                         | : Not available.   |
| <b>pH</b>   | : Not available.  |   |  |
| <b>Boiling point</b>                                    | : 100 °C (No. 5992)<br>100 - 187.2 °C (No.5968, 5972, 5991, 5994, 5997)<br>100 - 165°C (No.5973)<br>100 - 245.6 (No.5981)<br>100-190 (Nos. 5974, 5976)  | <b>Specific gravity</b>                       | : 1.0-1.4  |
| <b>Melting/Freezing point</b>                           | : Not available.  | <b>Coefficient of water/oil distribution</b>  | : Not available.   |
| <b>Vapor pressure (mmHg @ 20° C / 68° F)</b>            | : 0.6 -760<br>0.06 - 760 (No.5981)<br>760 (No.5983)<br>0.2 -760 (No.5990)<br>17 (Nos. 5976, 5974, 5992)   | <b>Solubility in water</b>                    | : Soluble  |
| <b>Vapor density (Air = 1)</b>                          | : Heavier than air.   | <b>Evaporation rate (n-Butyl acetate = 1)</b> | : Slower than n-butyl acetate  |
| <b>Volatile organic Compounds (VOC's) (lbs/gal;g/l)</b> | : 0.80 -0.85 /<br>95.00-102.58 (except as noted below)<br><br>0.22 (No. 5992)<br>0.17 / 20.84 (No.5979)<br>0.36 / 44.15 (No.5990)<br>0.77 / 92.46 (No.6001)<br>0.93 / 111.27 (No.6002)<br>1.04 / 125.59 (No.5980)<br>1.05 / 126.3 (No.5987)<br>1.12 - 1.18 / 134.42 -<br>142.59 (No.5968, 5981, 5986)<br>1.21 / 145.51 (No.5994)<br>1.31 / 157.86 (No.5972) | <b>Volatiles (% by weight)</b>                | : 61.17 (except as noted below)<br><br>47.31 (No.5971)<br>65.03 (No.5977)<br>52.3 (No. 5980)<br>53.92 (No.5982)<br>59.57 (No.5983)<br>50.85 (No.5985)<br>63.29 (No.5986)<br>57.65 (No.5988)<br>61.97 (No.5993)<br>61.73 (No.5996)<br>53.95 (No.5997)<br>55.48 (No. 5998)<br>47.72 (No.6001-6003)<br>60.52 (No. 5974)<br>60.87 (No. 5976)<br>50.66 (No. 5992) |
| <b>Viscosity</b>  | : Not available.  |   |  |
| <b>Special Remarks On Fire Hazards</b>                  | : Not flammable under normal conditions of use. This product will not burn, due to its water content. May spatter if the temperature exceeds the boiling point. Vapors may irritate eyes. May irritate skin.  |   |  |

**SECTION 10 - REACTIVITY AND STABILITY DATA**

**Stability and reactivity** : Stable under normal conditions.



**SUPERSATURATED**

MSDS No.:5965 - 6003

MSDS Preparation Date: April 1, 2012

Page 6 of 15

- Hazardous polymerization** : Will not occur.  
**Conditions to avoid** : High temperatures. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Oxidizing agents. Do not freeze.  
**Materials To Avoid And Incompatibility** : See Section 7 (Handling and Storage) section for further details.  
**Hazardous decomposition products** : See hazardous combustion products.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

| <u>Ingredients</u>  | <u>LC<sub>50</sub>(4hr)</u><br><u>inh, rat</u> | <u>LD<sub>50</sub></u>              |                       |
|---|--|-------------------------------------|-----------------------|
|   |  | <u>oral</u>                         | <u>dermal</u>         |
| <b>Supersaturated - Brilliant Red</b><br>Silica, crystalline quartz, respirable dust  | N/Av   | 500 mg/kg                           | N/Av                  |
| <b>Supersaturated - Paynes Gray</b><br>Iron oxide red   | N/Av   | >10000 mg/kg                        | N/Av                  |
| <b>Supersaturated - Paynes Gray</b><br><b>Supersaturated - Imperial Green</b><br>Carbon black   | 450 ppm/4H (rat)                               | 470 mg/kg (rat); 320 mg/kg (rabbit) | 400 mg/kg (rabbit)    |
| <b>Supersaturated Base - Velour Black</b><br>Silica, crystalline-cristobalite   | N/Av   | N/Av                                | N/Av                  |
| <b>Supersaturated Burnt Umber</b><br>Manganese dioxide  | N/Av   | 3478 mg/kg (rat)                    | N/Av                  |
| <b>Supersaturated Chrome Green</b><br>Chrome oxide  | N/Av   | N/Av                                | N/Av                  |
| <b>Supersaturated Chrome Yellow</b><br>Silica, crystalline-cristobalite   | N/Av   | N/Av                                | N/Av                  |
| Glycol ether  | N/Av   | 12,565 mg/kg (rat)                  | 11,890 mg/kg (rabbit) |
| <b>Supersaturated Green Shoe Blue, Supersaturated Emerald Green, Supersaturated Navy Blue, Supersaturated Grass Green</b><br>Propylene glycol | N/Av   | 20,000 mg/kg (rat)                  | 20,800 mg/kg (rabbit) |
| <b>Supersaturated Hunter Green</b><br>Silica, crystalline-cristobalite  | N/Av   | N/Av                                | N/Av                  |
| <b>Supersaturated Lemon Yellow, Supersaturated Van Dyke Brown, Supersaturated Base - Neutral</b><br>Silica, crystalline-quartz                | N/Av   | N/Av                                | N/Av                  |
| <b>Supersaturated Phthalo Green</b><br>1-Propanol, 2-amino-2-methyl-  | N/Av   | N/Av                                | N/Av                  |
| <b>Supersaturated White</b><br>No hazardous ingredients   | N/Av   | N/Av                                | N/Av                  |

**Toxicological data** : Low order of toxicity for normal industrial handling.

**SUPERSATURATED**

MSDS No.:5965 - 6003

MSDS Preparation Date: April 1, 2012

Page 7 of 15

- Carcinogenic status** : Contains crystalline silica. Crystalline silica is classified as carcinogenic by IARC (Group 1), the ACGIH (Category A2) and the NTP (Group 1 - Known human carcinogen). Contains crystalline silica; prolonged exposure by inhalation of particles can cause serious lung damage, including silicosis. Crystalline Silica has been classified as a carcinogen in dry powder form only. Exposure to respirable silica is not possible under normal conditions of use.  
 Nos. 5974, 5992, 5997, 6003: This product contains Carbon black, an IARC Group 2B carcinogen.
- Reproductive effects** : Not expected to have other reproductive effects.
- Teratogenicity** : Not expected to be a teratogen.
- Mutagenicity** : Nos. 5974, 5992, 5997, 6003: Contains Carbon black. Carbon black is suspected of causing mutations in non-reproductive cells, based on animal data.
- Reproductive Effects** : Not expected to have other reproductive effects.
- Irritancy** : Eyes, skin, respiratory system and digestive system.
- Sensitization to material** : Contains a chemical or chemicals which may cause skin sensitization. This product contains: Propylene glycol (No.5997, 5968, 5972, 5991, 5994); Chromium oxide (No.5971).
- Synergistic materials** : None reported by the manufacturer.

**SECTION 12 - ECOLOGICAL INFORMATION**

- Environmental effects** : None known or reported by the manufacturer.
- Important environmental characteristics** : None known or reported by the manufacturer.
- Ecotoxicological** : No data is available on the product itself.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

- Handling for Disposal** : See Section 7 (Handling and Storage) section for further details.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules. Do not puncture or incinerate. Contact waste disposal services.

**SECTION 14 - TRANSPORTATION INFORMATION**

| Regulatory Information                  | UN Number | Shipping Name  | Class         | Packing Group | Label   |
|---|-----------|----------------|---------------|---------------|---|
| TDG                                     | None      | Not regulated. | Not regulated | -None-        |  |
| <b>TDG Additional information</b>       | None.     |                |               |               |   |
| 49CFR/DOT                               | None      | Not regulated. | Not regulated | -None-        |  |
| <b>49CFR/DOT Additional information</b> | None.     |                |               |               |   |
| ICAO/IATA                               | None      | Not regulated. | Not regulated | -None-        |  |
| <b>ICAO/IATA Additional information</b> | None.     |                |               |               |   |
| IMDG                                    | None      | Not regulated. | Not regulated | -None-        |  |





**SUPERSATURATED**

MSDS No.:5965 - 6003

**MSDS Preparation Date:** April 1, 2012

Page 8 of 15

|                                    |       |
|------------------------------------|-------|
| <b>IMDG Additional information</b> | None. |
|------------------------------------|-------|

## SECTION 15 - REGULATORY INFORMATION

**US Federal Information:**

All ingredients are listed on the TSCA Inventory, or are exempted materials.

SARA Section 313: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical Constituents above de minimus concentrations.

**US State Right to Know Laws:**

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and/or reproductive harm. This product contains: Crystalline, silica. Carbon black is listed when found in unbound, airborne particles of respirable size. (No.5997)

**Canadian Regulations:**

Canadian Environmental Protection Act (CEPA): All ingredients are listed on the DSL, or are exempted materials.

Canadian WHMIS Classification: D2A, D2B; D2B (No.6002).

***This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.***

## SECTION 16 - OTHER INFORMATION

- Legend** : ACGIH: American Conference of Governmental Industrial Hygienists  
 IARC: International Agency for Research on Cancer  
 N/Ap: not applicable  
 N/Av: not available  
 NIOSH: National Institute of Occupational Safety and Health  
 NTP: National Toxicology Program  
 OSHA: Occupational Safety and Health Administration
- References** : Information obtained from sources including original supplier's Material Safety Data Sheet, and references including RTECS and CCOHS Cheminfo.

**Prepared for:**

**Rosco Laboratories Inc.**  
 52 Harbor View Avenue  
 Stamford, CT, United States  
 06902  
 Telephone: (203) 708 8900  
<http://http://www.rosco.com/>



**Prepared by:**

ICC The Compliance Center Inc.  
 Canada: 1-888-977-4834  
 USA: 1-888-442-9628

<http://www.thecompliancecenter.com>



### DISCLAIMER OF LIABILITY

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

**Preparation Date:** March 1, 2008

**MSDS Reviewed Date:** February 12, 2009





**Rosco Laboratories Inc.**  
52 Harbor View Avenue  
Stamford, CT, United States, 06902  
Phone: (203) 708 8900

---

**SUPERSATURATED**

MSDS No.:5965 - 6003

**MSDS Preparation Date:** April 1, 2012

Page 9 of 15

**Revision No.** : 2  
**Revision Information** : Added 5974, 5976, 5992.

**END OF DOCUMENT**

**SUPERSATURATED**

MSDS No.:5989

MSDS Preparation Date: April 1, 2012

Page 10 of 15

## MATERIAL SAFETY DATA SHEET

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**Product Name** : **SUPERSATURATED**

Supersaturated Turquoise

**Product Use** : Paint

**Chemical Family** : Mixture

**Supplier's name and address:**

**Rosco Laboratories Inc.**

52 Harbor View Avenue  
Stamford, CT, United States  
06902

**24 Hr. Emergency Tel #** : (800) 424-9300

**HMIS Rating** : \* - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

*Health:* \* 1      *Flammability:* 1      *Reactivity:* 0

**WHMIS Classes:**



TOXIC



### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

| <u>Ingredients</u>               | <u>CAS #</u> | <u>% (weight)</u> | <u>ACGIH TLV</u> |             | <u>OSHA PEL</u>              |             |
|----------------------------------|--------------|-------------------|------------------|-------------|------------------------------|-------------|
|                                  |              |                   | <u>TWA</u>       | <u>STEL</u> | <u>PEL</u>                   | <u>STEL</u> |
| 2-Butoxyethanol                  | 111-76-2     | 1.0 - 5.0         | 20 ppm           | N/Av        | 50 ppm (240 mg/m3)<br>(skin) | N/Av        |
| Silica, crystalline-quartz       | 14808-60-7   | 0.1 - 1.0         | 0.025 mg/m3      | N/Av        | (10)/(%SiO2<br>+ 2) mg/m3    | N/Av        |
| Silica, crystalline-cristobalite | 14464-46-1   | 1.0 - 5.0         | 0.025 mg/m3      | N/Av        | N/Av                         | N/Av        |
| Propylene glycol                 | 57-55-6      | 1.0 - 5.0         | N/Av             | N/Av        | N/Av                         | N/Av        |

### SECTION 3 - HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Liquid. Color as per product name. Irritating to eyes, respiratory system and skin. Harmful if inhaled or swallowed. Contains material which can cause cancer.

#### \*\*\*POTENTIAL HEALTH EFFECTS\*\*\*

**Target organs** : None reported by the manufacturer.

**Routes of exposure** : *Inhalation:* YES    *Skin Absorption:* YES    *Skin & Eyes:* YES    *Ingestion:* YES

**Potential acute health effects** :

*Eyes:* Causes eye irritation. May cause conjunctivitis, irritation, and inflammation of mucous membranes. May cause burning sensation, redness and tearing (watering). Possible severe irritation.

*Skin:* Irritating to skin. Possible irritation, defatting or dermatitis (rash). Components of the product may be absorbed into the body through the skin. May cause central nervous system depression.



**SUPERSATURATED**

MSDS No.:5989

MSDS Preparation Date: April 1, 2012

Page 11 of 15

**Inhalation:** Can cause irritation of the respiratory tract. Prolonged exposure to vapors may be harmful to health. If higher concentrations are inhaled, additional symptoms may include coughing, shortness of breath, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May cause mucous membrane irritation. Other adverse effects: Asphyxia. Severe lung irritation or lung damage, loss of appetite. Sanding and grinding dusts may be harmful if inhaled. Contains particles which may cause lung damage if inhaled in large quantities. Very toxic in particulate form upon inhalation.

**Ingestion:** Lung aspiration hazard. This product may be aspirated (inhaled) into the lungs during ingestion. May cause lung inflammation. May cause mucous membrane irritation. Ingestion may cause symptoms similar to inhalation. May cause gastrointestinal irritation. Gastrointestinal irritation may include abdominal pain, nausea, diarrhea and vomiting. Other adverse effects: intoxication. May cause central nervous system depression.

**Potential chronic health effects**

: Prolonged skin contact may defat the skin and produce dermatitis. May cause allergic skin reaction. Harmful by skin absorption. May cause central nervous system depression. Prolonged inhalation of vapors may cause lung damage, including chronic bronchitis. Contains crystalline silica; prolonged exposure by inhalation of particles can cause serious lung damage, including silicosis. Contains a chemical which may cause kidney damage. This product contains: 2-butoxyethanol.

**Medical conditions aggravated by overexposure**

: None expected, when used as intended.

**Additional health hazards**

: Exposure to respirable silica is not possible under normal conditions of use. Crystalline Silica has been classified as a carcinogen in dry powder form only.

**Potential environmental effects**

: None reported by the manufacturer.

**SECTION 4 - FIRST AID MEASURES**

**Inhalation** : If breathed in, move person into fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.

**Skin contact** : Flush with plenty of water. Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, seek prompt medical attention.

**Eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, seek prompt medical attention.

**Ingestion** : Call a physician or Poison Control Centre immediately. Do NOT induce vomiting. Guard against aspiration into lungs by having the individual turn on their left side.

**Notes For Physician** : Treat symptomatically.

**SECTION 5 - FIRE FIGHTING MEASURES**

**Fire hazards/conditions of flammability**

: Not flammable under normal conditions of handling. This product will not burn, due to its water content.

**Flammability classification (OSHA 29 CFR 1910.1200)**

: OSHA Combustible Liquid III B.

**Flash point**

: Not applicable.

**Flash point Method**

: Not applicable.

**Auto-ignition temperature** : Not available.

**Lower flammable limit (% by vol.)**

: Not applicable.

**Upper flammable limit (% by vol.)**

: Not applicable.

**Suitable extinguishing media**

: Dry chemical, foam, carbon dioxide and water fog.

**Explosion data: Sensitivity to mechanical impact / static discharge**

: Not expected to be sensitive to mechanical impact or static discharge.

**Special fire-fighting procedures/equipment**

: Firefighters should wear an approved full-face, self-contained breathing apparatus (SCBA) and impervious clothing. Water may be ineffective on fire, but may be helpful in cooling unburned containers. Do not use a solid water stream as it may scatter and spread fire. If water is used, fog nozzles are preferable.

**Hazardous combustion products**

: Oxides of carbon, nitrogen, and sulphur. Oxygen. Acrid fumes, toxic gases.



SUPERSATURATED

MSDS No.:5989

MSDS Preparation Date: April 1, 2012

Page 12 of 15

Oxidizing properties : None expected.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Avoid breathing vapors. Wear resistant clothing and boots.
- Environmental precautions** : Prevent product from entering drains, sewers, waterways and soil.
- Spill response/cleanup** : Eliminate all ignition sources if safe to do so. Ventilate area of release. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).
- Containment** : Should not be released into the environment. Recover free liquid or cover with inert absorbent material and place into appropriate container for disposal.

### SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Use with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Wash hands thoroughly after using this product, and before eating, drinking or smoking. Avoid breathing of dust created by cutting, sanding, or grinding. Sanding and grinding dusts may be harmful if inhaled. Do not re-use empty containers. Do not puncture container. Keep in properly labeled containers. Wear suitable protective equipment. Do not ingest.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Do not freeze. Keep container tightly closed when not in use. Store in upright position only. Keep out of the reach of children. Empty product containers may contain hazardous product residue.
- Incompatible materials** : Oxidizing agents. Acids and bases. Aluminum. Ammonium salts. Other: magnesium, chlorinated rubber.
- Special packaging materials** : Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

### SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Ventilation and engineering measures** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof equipment. Discharge exhaust only in area away from ignition sources.
- Respiratory protection** : Use NIOSH/MSHA approved full-face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
- Skin protection** : Gloves impervious to the material are recommended.
- Eye / face protection** : Safety glasses with side-shields or chemical splash goggles.
- Other protective equipment** : Emergency showers and eyewash facilities should be nearby. Depending on conditions of use, safety shoes and additional protective clothing may also be necessary.
- General hygiene considerations** : Wash hands thoroughly after using this product, and before eating, drinking or smoking. Wash hands before breaks and at the end of workday.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- |                               |                    |  |                             |
|-------------------------------|--------------------|--|-----------------------------|
| <b>Physical state</b>         | : Liquid.          | <b>Appearance</b>                            | : Color as per product name |
| <b>Odor</b>                   | : Not available.   | <b>Odor threshold</b>                        | : Not available.            |
| <b>pH</b>                     | : Not available.   |  |                             |
| <b>Boiling point</b>          | : 168.3 - 187.2 °C | <b>Specific gravity</b>                      | : 1.0-1.4                   |
| <b>Melting/Freezing point</b> | : Not available.   | <b>Coefficient of water/oil distribution</b> |                             |



**SUPERSATURATED**

MSDS No.:5989

MSDS Preparation Date: April 1, 2012

Page 13 of 15

|   |                     |   |                               |
|---|---------------------|---|-------------------------------|
| <b>Vapor pressure (mmHg @ 20° C / 68° F)</b>            | : 0.6 -760          | <b>Solubility in water</b>                    | : Soluble                     |
| <b>Vapor density (Air = 1)</b>                          | : Heavier than air. | <b>Evaporation rate (n-Butyl acetate = 1)</b> | : Slower than n-butyl acetate |
| <b>Volatile organic Compounds (VOC's) (lbs/gal;g/l)</b> | : 1.52 / 182.73     | <b>Volatiles (% by weight)</b>                | : 61.17                       |
| <b>Viscosity</b>  | : Not available.    |   |                               |

**Special Remarks On Fire Hazards**

: Not flammable under normal conditions of use. This product will not burn, due to its water content. May spatter if the temperature exceeds the boiling point. Vapors may irritate eyes. May irritate skin.

**SECTION 10 - REACTIVITY AND STABILITY DATA**

**Stability and reactivity** : Stable under normal conditions.

**Hazardous polymerization** : Will not occur.

**Conditions to avoid** : High temperatures. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Oxidizing agents. Do not freeze.

**Materials To Avoid And Incompatibility**  
: See Section 7 (Handling and Storage) section for further details.

**Hazardous decomposition products**  
: See hazardous combustion products.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

| <b>Ingredients</b>               | <b>LC<sub>50</sub>(4hr)</b><br><b>inh, rat</b> | <b>LD<sub>50</sub></b>              |                       |
|----------------------------------|--|-------------------------------------|-----------------------|
|                                  |  | <b>oral</b>                         | <b>dermal</b>         |
| 2-Butoxyethanol                  | 450 ppm/4H (rat)                               | 470 mg/kg (rat); 320 mg/kg (rabbit) | 400 mg/kg (rabbit)    |
| Silica, crystalline-quartz       | N/Av   | N/Av                                | N/Av                  |
| Silica, crystalline-cristobalite | N/Av   | N/Av                                | N/Av                  |
| Propylene glycol                 | N/Av   | 20,000 mg/kg (rat)                  | 20,800 mg/kg (rabbit) |

**Toxicological data** : Low order of toxicity for normal industrial handling.

**Carcinogenic status** : Contains Crystalline silica. Crystalline silica is classified as carcinogenic by IARC (Group 1), the ACGIH (Category A2) and the NTP (Group 1 - Known human carcinogen). Contains crystalline silica; prolonged exposure by inhalation of particles can cause serious lung damage, including silicosis. Crystalline Silica has been classified as a carcinogen in dry powder form only. Exposure to respirable silica is not possible under normal conditions of use.  
Contains 2-Butoxyethanol. 2-Butoxyethanol is classified as a confirmed animal carcinogen by ACGIH (Group A3).

**Reproductive effects** : Not expected to have other reproductive effects.

**Teratogenicity** : Not expected to be a teratogen.

**Mutagenicity** : Not expected to be mutagenic in humans.

**Reproductive Effects** : Not expected to have other reproductive effects.

**Irritancy** : Eyes, skin, respiratory system and digestive system.

**Sensitization to material** : Contains a chemical or chemicals which may cause skin sensitization. This product contains: Propylene glycol.

**Synergistic materials** : None reported by the manufacturer.

**SECTION 12 - ECOLOGICAL INFORMATION**

**Environmental effects** : None known or reported by the manufacturer.



**SUPERSATURATED**

MSDS No.:5989

**MSDS Preparation Date:** April 1, 2012

Page 14 of 15

**Important environmental characteristics**

: None known or reported by the manufacturer.

**Ecotoxicological**

: No data is available on the product itself.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

**Handling for Disposal**

: See Section 7 (Handling and Storage) section for further details.

**Methods of Disposal**

: Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules. Do not puncture or incinerate. Contact waste disposal services.

**SECTION 14 - TRANSPORTATION INFORMATION**

| Regulatory Information                  | UN Number | Shipping Name  | Class         | Packing Group | Label |
|---|-----------|----------------|---------------|---------------|-------|
| TDG                                     | None      | Not regulated. | Not regulated | -None-        |       |
| <b>TDG Additional information</b>       | None.     |                |               |               |       |
| 49CFR/DOT                               | None      | Not regulated. | Not regulated | -None-        |       |
| <b>49CFR/DOT Additional information</b> | None.     |                |               |               |       |
| ICAO/IATA                               | None      | Not regulated. | Not regulated | -None-        |       |
| <b>ICAO/IATA Additional information</b> | None.     |                |               |               |       |
| IMDG                                    | None      | Not regulated. | Not regulated | -None-        |       |
| <b>IMDG Additional information</b>      | None.     |                |               |               |       |

**SECTION 15 - REGULATORY INFORMATION**

**US Federal Information:**

All ingredients are listed on the TSCA Inventory, or are exempted materials.

SARA Section 313: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical Constituents above de minimus concentrations.

**US State Right to Know Laws:**

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and/or reproductive harm. This product contains: Crystalline, silica.

**Canadian Regulations:**

Canadian Environmental Protection Act (CEPA): All ingredients are listed on the DSL, or are exempted materials.

Canadian WHMIS Classification: D1A, D2A, D2B.

***This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.***





**SUPERSATURATED**


MSDS No.:5989

**MSDS Preparation Date:** April 1, 2012

Page 15 of 15

**SECTION 16 - OTHER INFORMATION**

- Legend** : ACGIH: American Conference of Governmental Industrial Hygienists  
 IARC: International Agency for Research on Cancer  
 N/Ap: not applicable  
 N/Av: not available  
 NIOSH: National Institute of Occupational Safety and Health  
 NTP: National Toxicology Program  
 OSHA: Occupational Safety and Health Administration
- References** : Information obtained from sources including original supplier's Material Safety Data Sheet, and references including RTECS and CCOHS Cheminfo.

|   |  |
|---|--|
| <p><b>Prepared for:</b><br/>         Rosco Laboratories Inc.<br/>         52 Harbor View Avenue<br/>         Stamford, CT, USA, 06902<br/>         Phone: (203) 708 8900<br/> <a href="http://http://www.rosco.com/">http://http://www.rosco.com/</a></p> |  |
| <p><b>Prepared by:</b><br/>         ICC The Compliance Center Inc.<br/>         Canada: 1-888-977-4834<br/>         USA: 1-888-442-9628<br/> <a href="http://www.thecompliancecenter.com">http://www.thecompliancecenter.com</a></p>                      |  |

**DISCLAIMER OF LIABILITY**

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

**Preparation Date:** : January 3, 2007

**MSDS Reviewed Date:** February 12, 2009

**END OF DOCUMENT**